



EN 1504-5

08

0761

DECLARATION OF PERFORMANCE

Sika[®] Injection-203

02	07	07	01	002	0	000002	1063
----	----	----	----	-----	---	--------	------

1. Product Type:

Unique identification code of the product-type: Sika[®] Injection

2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

-203
Refer to label

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Injection products for ductile filling of Cracks according to EN1504-5
U(D1) W(2) (1/2/3) (5/30)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Sika[®]
Sika[®] Services AG
Tüffenwies 16
CH-8048 Zürich
Switzerland
Factory No: 1063

5. Contact Address:

Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant (see 4)

6. AVCP:

System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:

System 2+

7. Notified body (hEN):

In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:

0761
Notified factory production control certification body No. 0761 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (FPC) 0062

8. Notified body (ETA):

In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued: **not relevant**

9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Adhesion and elongation capacity	~0,6 N/mm ² Elongation: > 10 %	EN 12618-2	EN 1504-5:2004
Watertightness	Watertight at 2 x 10 ⁵ Pa	EN 14068	
Workability crack widths 0,1 mm – 0,2 mm – 0,3 mm Moisture state of cracks: Dry or not dry	Injectability class Crack width: ≥ 0,2 mm Moisture state of cracks: Wet, damp and dry	EN 1771	
Durability	Lost deformation work < 20 %	EN 12637-1	
Corrosion behaviour	Assumably there are no corroding effects.	EN 1504-5 Article 4	
Release of dangerous substances	Conformity with 5.4	EN 1504-5	



TEMPLATE FOR LOCAL TRANSLATION, ONLY FOR INTERNAL USE

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Haktan Sahin
Corporate Product Engineer



Paul Schelbert
Material Group Manager

Sarnen, 12 February 2013,

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

For Further Information:
Insert Local address
Street
City & Post Code
Country

Phone Insert number
Telefax Insert number
www.sika.com

