



## DECLARATION OF PERFORMANCE

### Sikagard® 570 W Pele Elástica

|    |    |    |    |     |   |        |      |
|----|----|----|----|-----|---|--------|------|
| 01 | 09 | 15 | 10 | 100 | 0 | 000030 | 1049 |
|----|----|----|----|-----|---|--------|------|

|  |   |
|--|---|
| <b>1. Product Type:</b><br>Unique identification code of the product-type  | Sikagard®   |
| <b>2. Type</b> batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):                      | 570 W Pele Elástica   |
| <b>3. Intended use</b> or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:   | Products and systems for the protection and repair of concrete structures.<br>Part 2: Surface protection systems for concrete.  |
| <b>4. Name, registered trade name</b> or registered trade mark and contact address of the manufacturer as required under Article 11(5):                              | Sikagard®   |
| <b>5. Contact Address:</b><br>Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): | Sika Portugal, SA<br>Rua de Santarém -113<br>4401-601 Vila Nova de Gaia<br>Portugal   |
| <b>6. AVCP:</b><br>System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:              | System 2+   |
| <b>7. Notified body:</b><br>In case of declaration of performance concerning a construction  | <b>0866</b><br>Notified factory production control certification body No. <b>0866</b> performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control, <b>0866-CPD-2008/CE.0097</b> . |
| <b>8. Notified Body:</b><br>In case of the declaration of performance concerning a construction product for which an European Technical Assessment has been issued:  | Not relevant (see 7)  |

Declaration of Performance



**9. Declared performance:**

| Essential Characteristics               | Performance  | Test Standard    | Harmonised Technical Specification |
|---|--|------------------|------------------------------------|
| Permeability to carbon dioxide          | Sd > 50 m  | EN 1062-6        | EN 1504-2: 2 2004                  |
| Permeability to water vapour            | Sd > 5 m (Class I)                                       | EN ISO 7783-1/-2 |                                    |
| Water absorption and water permeability | (w < 0.1 kg/m <sup>2</sup> .h <sup>1/2</sup><br>Class II | EN 1062-3        |                                    |
| Bond strength by puul-off               | ≥ 1,0 (0,7) N/mm <sup>2</sup>                            | EN 1542          |                                    |
| Crack bridging properties resistance    | A5 (23°C)  | EN 1062-7        |                                    |
| Reaction to fire                        | Class F  | EN 13501         |                                    |

## 10. Declaration:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Richard Aubertin  
General Manager



Patrícia Lopes  
TMM Roofing

Vila Nova de Gaia, 14 November 2013

---

## Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

---

---

### Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

---

