



DECLARATION OF PERFORMANCE

Sikafloor® - Proseal

01	08	03	04	005	0	000004	1049
----	----	----	----	-----	---	--------	------

1. Product Type: Unique identification code of the product-type:	Sikafloor®-
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	Proseal, batch nr refer to packaging
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Solvent based, clear acrylic resin polymer solution used to cure, harden and seal fresh or hardened concrete EN 13813 SR-B1,5
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sikafloor®-
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Sika Portugal, SA Rua de Santarém, 113 4400-292 Vila Nova de Gaia Portugal
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 4
7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	
8. Notified body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	Not relevant (refer to item 7)

Declaration of Performance



9. Declared Performance

Essential characteristics	Performance	Test Standard	Harmonised technical Specification
Reaction to fire	NPD ¹⁾	EN 13501-1	EN 13813
Release of corrosive substances (Synthetic Resin Screed):	SR	EN 13813	
Water permeability	NPD	EN 1062-3	
Abrasion Resistance:	NPD	EN 13892-4	
Bond strength:	B 1,5	EN 13892-8	
Impact Resistance:	NPD	EN ISO 6272	
Sound insulation:	NPD	EN ISO 140-1	
Sound absorption:	NPD	EN ISO 354	
Thermal resistance	NPD	EN 12664	
Chemical resistance	NPD	EN 13529	

- 1) Min. classification, please refer to the individual test certificate.
 NPD - Desempenho não determinado (Not performance determined)



10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



(Richard Aubertin)
General Manager



(Luis Duarte)
Target Market Manager

Vila Nova de Gaia, 31 May 2013

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

