



DECLARATION OF PERFORMANCE

Sikagard®-660 ES

01	03	03	02	001	0	000008	1049
----	----	----	----	-----	---	--------	------

1. Product Type:

Unique identification code of the product-type

Sikagard®

2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

-660 ES

Batch Number (refer to label)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For surface protection – coating, of absorbent substrates such as concrete in civil engineering or building concrete structures.

Suitable for protection against ingress (Principle 1, method 1.3 of EN 1504-9),
Suitable for moisture control (Principle 2, method 2.3 of EN 1504-9)
Suitable for increasing the resistivity (Principle 8, method 8.3 of EN 1504-9)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Sikagard®

Sika Portugal – Produtos Construção e Indústria SA
Rua de Santarém, 113
4400-292 Vila Nova de Gaia – Portugal

5. Contact Address:

Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not relevant (see 4)

6. AVCP:

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+

7. Notified body:

In case of declaration of performance concerning a construction

0866

Notified factory production control certification body No. **0866** performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control, **0866-CPD-2008/CE.0097**.

8. Notified Body:

In case of the declaration of performance concerning a construction product for which an European Technical Assessment has been issued:

Not relevant (see 7)



9. Declared performance:

Essential Characteristics	Performance	Test Standard	Harmonised Technical Specification
Permeability to CO ₂	S _D > 50 m	EN 1062-6	EN 1504-2: 2 2004
Water vapour permeability	S _D < 5 m (class I)	EN ISO 7783-1 EN ISO 7783-2	
Capillary absorption and permeability to water	$\omega < 0,1 \text{ kg/m}^2 \cdot \text{h}^{0,5}$	EN 1062-3	
Ageing (UV and humidity, 2000h)	No blistering, no cracking, no flaking, darkening	EN 1062-11	
Abrasion resistance (Taber test)	Mass loss < 3 000 mg abraser wheel H22/ rotation 1000 cycles/ load 1000 g	EN ISO 5470-1	
Diffusion of chloride ions	$3,5 \times 10^{-16} \text{ m}^2/\text{s}$	LNEC specification E 468	
Cross cut	≤ GT 2	EN ISO 2409	
Reaction to fire	Class F	EN 13501-1	

10. Declaration:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Richard Aubertin
General Manager



Cláudia Gomes
TMM Refurbishment

Vila Nova de Gaia, 19 June 2013

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

