Repair & Protection
Declaration of Performance
Edition 05.2013
Identification no. 01 03 03 06 002 0 000002
Version no. 1



EN 1504-2:2004

09

0866

DECLARATION OF PERFORMANCE

Sikagard®-552 W Aquaprimer

01	03	03	06	002	0	000002	1049

1. Product Type:

Unique identification code of the product-type

- **2. Type** batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):
- **3. Intended use** or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Sikagard[®]

-552 W Aquaprimer

Batch Number (refer to label)

Priming coat for concrete and dense mineral substrates like fibre cement, aerated concrete, gypsum and thin rendering.

Sikagard®-**552 W Aquaprimer** can also be used as a primer on firmly adhering existing water based coatings.

Sikagard®-552 W Aquaprimer is part of the system:

- Suitable for protection against ingress (Principle 1, method 1.3 of EN 1504-9),
- Suitable for moisture control (Principle 2, method 2.3 of EN 1504-9)
- Suitable for increasing the resistivity (Principle 8, method 8.3 of EN 1504-9)
- **4. Name, registered trade name** or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Sikagard[®]

5. Contact Address:

Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not relevant (see 4)

6. AVCP:

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+

7. Notified body:

In case of declaration of performance concerning a construction covered by a harmonised standard

0866

Notified factory production control certification body No. **0866** performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control, **0866-CPD-20087CE.0097.**



Repair & Protection Declaration of Performance Edition 05.2013 Identification no. 01 03 03 06 002 0 000002 Version no.1

8. Notified Body:

In case of the declaration of performance concerning a construction product for which an European Technical Assessment has been issued:

Not relevant (see 7)

9. Declared performance:

Essential Characteristics	Performance	Test Standard	Harmonised Technical Specification	
Permeability to CO ₂	NPD	EN 1062-6		
Water vapour permeability	NPD	EN ISO 7783-1 EN ISO 7783-2		
Capillary absorption and permeability to water	NPD EN 1062-3			
Thermal compatibility (Freeze and thaw cycling with de-icing salt immersion)	NPD	EN 13687-1	EN 1504-2: 2004	
Adhesion Strength by pull-off test	NPD	EN 1542		
Reaction to fire after application	Class F	EN 13501-1		
Artificial weathering	NPD	EN 1062-11		
Dangerous substances	comply with 5.3			

Note: **Sikagard®-552 W Aquaprimer** is CE marked as part of the system of Sika protective coating and as such does not have any specific performance data's



Repair & Protection **Declaration of Performance** Edition 05.2013 Identification no. 01 03 03 06 002 0 000002 Version no.1

10. Declaration:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Richard Aubertin

sedit

General Manager

Cláudia Gomes

TMM Refurbishment

Vila Nova de Gaia, 31 May 2013

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request



Sika Portugal, SA Portugal

R. de Santarém, 113 Tel. +351 22 377 69 00 4400-292 V. N. Gaia Fax +351 22 370 20 12 www.sika.pt