



EN 1504-3:2005

08

0099

DECLARATION OF PERFORMANCE

Sika MonoTop®-612

01	03	02	04	001	0	000004	1053
----	----	----	----	-----	---	--------	------

1. Product Type: Unique identification code of the product-type:	Sika MonoTop® -
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	612 , (batch nr. see packaging)
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	1-component class R3 CC mortar for the repair of concrete structures Principles 3, 4 and 7 - methods 3.1, 3.3, 4.4, 7.1 and 7.2 Conforming to the Annex ZA Table ZA.1
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sika MonoTop® Sika S.A.U Crta. Fuencarral 72, 28108 Alcobendas Madrid-Spain
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not relevant (see 4)
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 2+
7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	0099 Notified factory production control certification body No. 0099 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (FPC) 0099/CPR/B15/0009.

Declaration of Performance



<p>8. Notified body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:</p>	<p>Not relevant (refer to item 7)</p>
---	--

9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Compressive Strength	≥ 25 MPa	EN 12190	EN 1504-3: 2005
Chloride Ion Content	≤ 0.05 %	EN 1015-17	
Adhesive Bond	≥ 1.5 MPa	EN 1542	
Controlled Expansion/Retraction	≥ 1.5 MPa	EN 12617-4	
Carbonation Resistance	$d_k \leq$ control concrete (MC(0.45))	EN 13295	
Elastic Modulus	≥ 15 GPa	EN 13412	
Capillary Absorption	≤ 0.5 kg.m ⁻² .h ^{-0.5}	EN 13057	
Fire Reaction	Euroclass A1	EN 13501-1	



10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Raúl Díez Bueno
Technical Department

Ángel González Lucas
General Manager

Alcobendas, 21 May 2013

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Para más información:
Sika S.A.U
Crta. Fuencarral, 72
28108 Alcobendas
Madrid

Teléfono +34 91 657 23 75
Fax +34 91 662 19 38
www.sika.com