Repair & Protection EC Declaration of Performance Edition December 2013 Identification no. 01 03 03 01 001 0 000001 Version no. 2



EN 1504-2:2004

09

0866

DECLARATION OF PERFORMANCE Sikagard®-700 S

01 03 03 01 001 0 000001 1049

1. Product Type: Unique identification code of the product-type:	Sikagard [®]	
2. Type batch or serial number or any other element	-700 S	
allowing identification of the construction product as required under Article 11(4):	Batch Number (refer to packaging)	
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the	Water-repellent impregnation (hydrophobic treatment) for absorbent substrates such as concrete in civil engineering or building concrete structures	
manufacturer:	Suitable for protection against ingress (Principle 1, method 1.1 of EN 1504-9),	
	Suitable for moisture control (Principle 2, method 2.1 of EN 1504-9)	
	Suitable for increasing the resistivity (Principle 8, method 8.1 of EN 1504-9)	
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sikagard [®]	
	Sika Portugal – Produtos Construção e Indústria, SA Rua de Santarém, 113	
	4400-292 Vila Nova de Gaia - Portugal	
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not relevant (see 4)	
6. AVCP: System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:	System 2+	
7. Notified body: In case of the declaration of performance concerning a construction product covered by a harmonized standard:	0866 Notified factory production control certification body No. 0866 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control 0866-CPD-2008/CE.0097	
8. Notified body: In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:	Not relevant (see 7)	



Repair & Protection EC Declaration of Performance Edition December 2013 Identification no. 01 03 03 01 001 0 000001 Version no. 2

9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Depth of penetration:	Class I: <10 mm	EN 1504-2 Table 3	
Water absorption and resistance to alkali as:		EN 13580	
Absorption ratio:	< 7.5% compared with the untreated specimen		EN 1504-2: 2004
Absorption ratio:	< 10% after immersion in alkali solution		
Drying rate:	Class I: > 30%	EN 13579	
Resistance to freeze thaw salts stress:	NPD	EN 13581	



Repair & Protection EC Declaration of Performance Edition December 2013 Identification no. 01 03 03 01 001 0 000001 Version no. 2

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Richard Aubertin Director Geral

redit

Claudia Gomes TMM Refurbishment

Vila Nova de Gaia, 16 December 2013

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Legal note

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

