



EN 1504-6:2006

08

0099

## DECLARATION OF PERFORMANCE

### SikaGrout®-295

01	02	01	01	001	0	000060	1053
----	----	----	----	-----	---	--------	------

<b>1. Product Type:</b> Unique identification code of the product-type:	<b>SikaGrout® -</b>
<b>2. Type</b> batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	<b>295</b> (batch nr. see packaging)
<b>3. . Intended use</b> or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	1-component. Product for anchoring steel bars. CC Product Conforming to the Annex ZA Table ZA.1
<b>4. Name, registered trade name</b> or registered trade mark and contact address of the manufacturer as required under Article 11(5):	<b>SikaGrout®</b> Sika S.A.U Crta. Fuencarral 72, 28108 Alcobendas Madrid-España
<b>5. Contact Address:</b> Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	No relevant (see 4)
<b>6. AVCP:</b> System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:	System 2+
<b>7. Notified body (hEN):</b> In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	Asociación Española de Normalización y Certificación (AENOR), Notified body Number 0099  Conformity certification of the Factory production control on the base to:  Initial inspection of the manufacturing plant and factory production control  Monitoring and continuous evaluation and approval of Factory production control  Certificate number 0099/CPR/B15/0006

Declaration of Performance



<b>8. Notified body (ETA):</b> In case of the declaration of performance (DoP) concerning a construction product for which a European Technical Assessment has been issued: (ETA):	No relevant (refer to item 7)
---	-------------------------------


## 9. Declared performance

Essential characteristics	Performance	Standard	Harmonized Technical Specification
Resistant to the pulling up	Displacement $\leq$ 0.6mm (load of 75kN)	EN 1881	EN 1504-6:2006
Ion chloride content	$\leq$ 0.05%	EN 1015-17	
Reaction to fire	A1 fl	EN 13501-1	

## 10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Mónica Sangil García  
 Technical Department

Ángel González Lucas  
 General Manager

Alcobendas, 25 February 2013

## Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

### Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



For more information:  
 Sika S.A.U  
 Crta. Fuencarral, 72  
 28108 Alcobendas  
 Madrid

Telephone +34 91 657 23 75  
 Fax +34 91 662 19 38  
 www.sika.com